



Suppliers of passive fire products, acoustic and specialist insulation
Manufacturers of the Safire® Fire Stopping Range

Safire® High Temperature Adhesive/Sealant

DESCRIPTION

Safire® High Temperature Adhesive and sealant is a silicate based material for use where a high temperature resistant seal or adhesive bond is required.

The product dries to a hard, cement-like material with good adhesion to many surfaces. It has a continuous operating temperature up to a maximum of 1250°C. After subjected to high temperature above 800°C the product sets to a solid ceramic mass which is resistant to thermal shock.

Suitable for use where resistance to spread of flame is required.

It is supplied as a ready to use, easily extrudable paste in a 310ml cartridge.

APPLICATIONS

For bonding and sealing between a wide range of materials such as metal, glass, ceramic, concrete, stone, clay and silicate(glass) fibre.

Provides a high temperature, rigid seal around pipework and flues in fireplaces, boilers, solid fuel burners and central heating systems.

General fire protection applications where a rigid seal is required.

LIMITATIONS

Safire® High Temperature Adhesive and Sealant will not bond plastics materials, particularly where flexing may occur.

TECHNICAL DETAILS

Density:	1.75-1.85g/cm ³
Flash Point:	does not support combustion
pH:	13
Application Temperature Range:	5oC to 40oC
Service Temperature Range:	-20oC to 1250oC (starts to soften at 1200oC; melts at 1300oC)
Slump Resistance:	Excellent. Soft highly thixotropic paste.
Initial Drying:	Skins within 5 minutes (20oC and 65% RH)
Through drying:	Approx. 5mm/day (20oC and 65% RH)
Oxidation resistance:	Excellent
Acid Resistance:	Excellent (except for hydrofluoric acid)
Shelf Life:	12 months in unopened containers stored in cool, dry conditions.(5oC to 30oC)
Colour:	natural (buff) other colours available on request.
Coverage:	45m for a 3mm diameter bead for a 310ml cartridge

APPLICATION INSTRUCTIONS

All surfaces must be clean and dry and free from dirt, dust, grease and other contamination. Light abrasion of the surfaces to be bonded will improve the adhesion.

cont.

Fireus Ltd.

Unit 6 Thetis Road, Lune Industrial Estate, Lancaster, LA1 5QP

Tel. 01524 388898 | Fax. 01524 383724 | Email. info@fireus.co.uk | Web. www.fireus.co.uk

Safire® High Temperature Adhesive/Sealant

Apply the adhesive from the cartridge, forcing it onto the area to be sealed, then immediately tool it down to ensure good adhesion. Complete tooling within 5-10 minutes.

When bonding materials, apply a bead of adhesive to one surface and immediately combine the two parts, applying pressure to ensure good surface contact.

Application equipment should be cleaned with warm water after use.

STORAGE

Store in cool dry conditions. (5oC to 30oC)

HEALTH AND SAFETY

See Health & Safety data sheet before using the product. Should any of the adhesive come into contact with eyes, then flush eyes liberally with clean water and seek medical advice. If accidentally ingested, seek medical attention and show the container or label.

KEEP AWAY FROM CHILDREN AND ANIMALS.

Further Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate