



passive fire protection and insulation

Suppliers of passive fire products,  
acoustic and specialist insulation  
Manufacturers of the Safire® Fire Stopping Range


## Safire® Fire Stop Block

Safire® Fire Stop Block is a unique, compressible and fully intumescent alternative to fire pillows.



### Key Features

- 2 hour fire rated
- easily cut to length
- other pre-cut sizes available
- red coating for easy recognition
- easy to add and remove
- square edges easy to stack
- no overlapping required
- can be installed from one side
- 150mm length can provide a clean wall solution
- compressible material for easy installation

### Technical Details

Description:  
Compressible fully intumescent firestop seal for service penetration openings.

Dimensions:  
30mm x 150mm x 1000mm

Typical Usage:  
150mm x 50mm = 0.3 lengths  
100mm x 100mm = 0.3 - 0.4 lengths  
150mm x 150mm = 0.75 - 0.9 lengths

### Test Data

Tested to BS EN 1363-1:1999 for upto 120 mins.  
Test Report No. IF011059 Chiltern Int. Fire

EI120 on upto 100mm x 100mm PVC trunking  
EI120 on upto 150mm x 150mm steel trunking  
EI120 on Cable Basket and various cable types



**SAFIRE** a brand of Fireus Ltd.

Fireus Ltd.

Unit 6 Thetis Road, Lune Industrial Estate, Lancaster, LA1 5QP

Tel. 01524 388898 | Fax. 01524 383724 | Email. [info@fireus.co.uk](mailto:info@fireus.co.uk) | Web. [www.fireus.co.uk](http://www.fireus.co.uk)

[www.fireus.co.uk](http://www.fireus.co.uk)  
01524 388898

The Fire Stop Block can be supplied in lengths up to 1 metre and is easily cut to size on site. This ensures maximum flexibility and obviates waste.

The material can be installed within and around various electrical penetrations and provides up to 2 hours fire resistance.

## Technical Details

**Description:**  
Compressible fully intumescent firestop seal for service penetration openings.

**Dimensions:**  
30mm x 150mm x 1000mm

**Typical Usage:**  
150mm x 50mm = 0.3 lengths  
100mm x 100mm = 0.3 - 0.4 lengths  
150mm x 150mm = 0.75 - 0.9 lengths

## Test Data

Tested to BS EN 1363-1:1999 for up to 120 mins.  
Test Report No. IF011059 Chiltern Int. Fire

EI120 on up to 100mm x 100mm PVC trunking  
EI120 on up to 150mm x 150mm steel trunking  
EI120 on Cable Basket and various cable types



Other products in the Fireus Products range:

**FIRE BARRIERS:** Total Comfort Rock Fibre Fire Blanket

**FIRE STOPPING:** Compound  
Fire Collars  
Barriers (Batts)  
Sealants  
Fire Pillows  
Expansion Joints  
Flamestop60  
Flamestop FSI

**THERMAL:** Industrial thermal and acoustic insulation

For information on any of the above, or the name of your nearest distributor, please contact our sales department on tel. 01524 388898.

Alternatively, product information is available from our web site at [www.fireus.co.uk](http://www.fireus.co.uk)

Your distributor:



**Fireus Ltd.**

Unit 6 Thetis Road, Lune Industrial Estate, Lancaster, LA1 5QP

Tel. 01524 388898 | Fax. 01524 383724 | Email. [info@fireus.co.uk](mailto:info@fireus.co.uk) | Web. [www.fireus.co.uk](http://www.fireus.co.uk)